

# ANTI-STATIC NEUTRAL/RESTORER CLEANER DATA SHEET

## **APPLICATION**

- Before application, dry mop area to be cleaned.
- Dilute CLEANER 10 to 1.
- Thoroughly mix concentrate. Use a clean rayon mop. Do not flood, rinse the floor. Wring out excess cleaner. Allow floor to dry.
- Allow to dry before walking on floor.
- Do not damp mop with plain water, high alkaline or high residue cleaners. This will damage a floor's static dissipative properties.
- Heavy to moderate traffic areas should be cleaned once a week.
- Light traffic areas should be cleaned 2-3 times a month.
- Apply a 50-50 coat of Anti-Static Floor Finish and water if necessary to restore proper ESD levels.

## **STORAGE**

- Store tightly closed in a cool dry area.

## **SPECIFICATIONS**

<b>Active Ingredients:</b>	<b>Proprietary static dissipative compounds</b>
<b>Surface Resistance (RTT)</b>	<b>10 to the 7<sup>th</sup>-10 to the 9<sup>th</sup> @ 100 volts</b>
<b>Electrostatic Decay Time</b>	<b>0.1 Seconds</b>
<b>pH</b>	<b>6.5 - 7.5</b>
<b>Color</b>	<b>Yellow</b>
<b>Odor</b>	<b>Mild Lemon</b>
<b>Solubility in Water</b>	<b>100%</b>
<b>Freeze/Thaw Stability</b>	<b>Minimum 3 cycles</b>
<b>Shelf life</b>	<b>1 year</b>
<b>Flash Point</b>	<b>None</b>
<b>Weight Per Gallon</b>	<b>8.56 lbs./gallon</b>
<b>Biodegradable</b>	<b>Yes</b>
<b>Soil Suspension</b>	<b>Very Good</b>

Health	1
Flammability	0
Reactivity	0
Personal Protection	B

## **DynaSol, Inc.**

330 Pine Street  
Canton, Ma 02021  
781-821-8888