

SUPERSEAL

Technical Data Sheet

Urethane/Acrylic Floor Sealer

DESCRIPTION

A urethane/acrylic floor sealer formulated for ultra-high gloss, toughness and superior wear. SUPERSEAL contains urethane, acrylic, polyethylene and polypropylene, all combined in a unique surfactant system, that enables SUPERSEAL to penetrate and adhere to resilient surfaces. When applied as directed, SUPERSEAL reduces powdering and enhances the appearance of the subsequent floor finish. SUPERSEAL dramatically reduces the necessity of stripping.

USES:

As a sealer for hard or resilient surfaces such as vinyl, vinyl asbestos, and asphalt tile. Also on rubber, terrazzo and all sealed masonry surfaces. For industrial and institutional uses only.

LIQUID PROPERTIES:

SOLIDS:	20.0 ± 0.5%
pH:	9.5 ± 0.3%
COLOR:	Milk White
DENSITY:	8.75 lbs. per gallon
FLAMMABILITY:	Non Flammable
SHELF LIFE:	1 year 22°C, 45 days 50°C
STABILITY:	Passes 3 freeze-thaw cycles

FILM PROPERTIES:

CLARITY:	Clear
COLOR:	Colorless
COLOR STABILITY:	Non yellowing, U.V. tested for 72 hours. Contains color stable acrylics and urethanes.
GLOSS:	Two coats, 60 Photovolt Glossmeter: Vinyl 90; Black Glass 95.
SLIP RESISTANCE:	Meets or exceeds ASTM method D 2047 - 82.

COVERAGE:

2,000 square feet per gallon for normal application.

DIRECTIONS:

1. Strip area to be coated.
2. Rinse floor thoroughly and allow to dry.

3. Apply 2-3 thin coats of SUPERSEAL, using cross coat technique. Allow 20-30 minutes drying time between coats. (Local variations in temperature and humidity can affect drying times)
4. Allow last coat of SUPERSEAL to dry for 1 hour. the final coats of finish can then be applied.

CAUTIONS:

Contains Diethylene Glycol Methyl Ether.

Avoid contact with skin and eyes. Gloves and eye protection are recommended.

KEEP OUT OF REACH OF CHILDREN

EMERGENCY ACTIONS:

For external skin contact, remove contaminated clothing. Immediately flush skin or eyes with cold running water. If eye is contacted, seek medical assistance.

If ingested, induce vomiting. Seek medical assistance at once! Maintain normal body temperature to avoid shock.

Gloves recommended when using this product.



 **SPECTROWAX CORPORATION**

America's choice for all things custodial

70 Hichborn Street/Boston, Massachusetts 02135
Phone: (617) 254-2800/1-800-545-5444