

# ANTISTATIC FLOOR FINISH

## Technical Data Sheet

### STATIC DISSIPATIVE FLOOR FINISH

#### DESCRIPTION:

A static dissipative floor finish designed to control floor static. Unlike other static dissipative floor finishes, ANTISTATIC FLOOR FINISH has been formulated in a manner that allows it to be an easily maintained floor finish. A unique polymer system maintains uniform dissipation throughout the entire thickness of film. It can be maintained with either low or high speed equipment.

#### USES:

For use on vinyl, vinyl composition, asphalt, rubber terrazzo and all sealed masonry surfaces. May be used on conductive floors.

#### LIQUID PROPERTIES:

SOLIDS	20.0% ± 0.5%
pH	8.6 ± 0.2%
COLOR	Milk White
DENSITY	8.75 #/gal
FLAMMABILITY	Non-Flammable
SHELF LIFE	1 yr @ 22°C, 45 days @ 50°C
STABILITY	Passes 3 Freeze Thaw Cycles per ASTM D3209-82

#### FILM PROPERTIES:

CLARITY	Clear
COLOR	Colorless
COLOR STABILITY	Non-yellowing, U.V. tested for 72 hours
GLOSS	88 min per ASTM D1455-82
SLIP RESISTANCE	Meets or exceeds ASTM D2047-82
SURFACE RESISTIVITY	10 <sup>7</sup> - 10 <sup>9</sup> OHMS/SQ @ 40% R.H. per ASTM D257-78
ELECTROSTATIC DECAY TIME	5,000 volt charge to zero in less than 0.1 seconds per MIL-B-81705B, Fed Test Method Standard 101B, Method 4046
STATIC CHARGE GENERATION	Zero per AATCC Step Test Method 134-1979

#### DIRECTIONS:

- 1 Clean or strip area to be coated.
- 2 Rinse floor thoroughly and allow to dry.
- 3 Apply 3-4 thin coats using cross coat technique. Allow to dry for 30 minutes between coats.

#### MAINTENANCE

- 1 Sweep or dry mop the area to be maintained.
- 2 Damp mop with a tightly wrung mop using a dilute, non-ionic cleaner. Allow to dry.
- 3 For spray buffing, dilute product 1:4 with water and use as a spray buff.
- 4 For high speed maintenance, apply a thin coat of product cut 1:3 with water. Allow to dry and burnish using high speed pads and equipment.

#### CAUTIONS:

Contains Diethylene glycol methyl ether  
Wear rubber gloves and eye protection when using this product.

#### KEEP OUT OF THE REACH OF CHILDREN

#### EMERGENCY ACTIONS:

If ingested, induce vomiting. Seek medical attention at once!  
If eye is contacted, flush with water and seek medical help.  
For external skin contact, remove contaminated clothing and wash thoroughly with water.



#### SPECTROWAX CORPORATION

*America's choice for all things custodial*  
70 Hichborn Street/Boston, Massachusetts 02135  
Voice (617) 254-2800/ (800) 545-5444 FAX (617) 782-0176