

DYNA-QUICK

Technical Data Sheet

HEAVY DUTY STRIPPER

DESCRIPTION:

DYNA-QUICK is a non-ammoniated stripper for applications where special strength strippers are required. DYNA-QUICK has been formulated to attack today's metal crosslinked finishes with minimal odor.

DILUTIONS:

For HEAVY Dewaxing - Dilute 1 part DYNA-QUICK to 3 parts water.

For NORMAL Dewaxing - Dilute 1 part DYNA-QUICK to 6 parts water.

For Light Dewaxing - Dilute 1 part DYNA-QUICK to 8 parts water.

USES:

For vinyl and vinyl composition tile floors. Not for use on cork.

LIQUID PROPERTIES:

| | |
|--------------------|-----------------------------|
| CONCENTRATE pH.... | 12.0 |
| COLOR..... | Blue |
| DENSITY..... | 8.4 #/GAL |
| FLAMMABILITY..... | Non-Flammable |
| SHELF LIFE..... | 1 Year 22°C 30 Days 50°C |
| STABILITY..... | Freeze-Thaw Stable |
| ODOR..... | Mild - Neutral |

DIRECTIONS:

- 1 Apply diluted solution liberally to floor surface. DO NOT treat more than 250 sq ft at one time
- 2 Allow solution to remain on floor for 2-5 minutes before scrubbing
- 3 Scrub thoroughly using either black, brown or high productivity pads.
- 4 Remove solution with vacuum or mop.
- 5 Rinse floor thoroughly with cold water.

CAUTIONS:

Contains Monoethanolamine (CAS#141-43-5)

Wear rubber gloves and eye protection when using this product.

Not recommended for use on rubber, asphalt or hardwood floors.

KEEP OUT OF THE REACH OF
CHILDREN

EMERGENCY ACTIONS:

If ingested, do not induce vomiting. Drink water or milk and seek medical attention at once! If eye is contacted, flush with water and seek medical help. For external skin contact, remove contaminated clothing and wash thoroughly with water.



DYNASOL
330 Pine ST. Canton, MA 02021
1-781-821-8888