



# DynaSol

## GREEN LIGHT FLOOR FINISH

### Description:

This environmentally preferable metal free floor finish contains no zinc or other heavy metals that can be harmful to waste treatment plants. This low odor finish has exceptional durability and flexibility and can be maintained with scrub and recoat procedures, spray buffing or high speed burnishing.

GREEN LIGHT is formulated to meet both Green Seal's™ GS-40 and EPA's Designed for the Environment programs when used at the prescribed dilution.

### Liquid Properties:

Color	Milkey White
Odor	Mild Acrylic
Non-Volatile Solids (ASTM D2834)	25% +/- .5
Density	8.80 lbs./Gal
Specific Gravity	1.055
pH	8.0-8.5
(ASTM E70)	
Slip Resistance (ASTM D2047)	>0.50 COF
Recoatability (ASTM D3153)	Exceeds
Freeze Thaw Stability (ASTM D3209)	Passes
Detergent Resistance (ASTM D3207)	Exceeds
Removability (ASTM D1792)	Exceeds
Soil Resistance (ASTM D3206)	Excellent
Dry/Recoat Time	30 min.
Coverage, Approximate	Up to 3,000 ft per gal.
Package Size	Gallons (4x1)Cases 5 Gallon Pails 30 Gallon Drums 55 Gallon Drums

**DISPOSAL:** Please dispose of this product and waste generated from this product in accordance with all applicable local state, and federal regulations. Please recycle container.

### Directions:

Read entire label before using this product. Recommended for use on all types of resilient tile flooring and properly prepared hard surfaces.

### RESTORATIVE-MAINTENANCE:

Completely remove all old wax, finish and soil from floor surface following strip procedure instruction on stripper label. Floor surface must be clean, dry and free of residue before finish is applied. Apply finish in uniform, thin to medium coats using a clean synthetic finish mop or applicator systems. Allow each coat to dry thoroughly before applying additional coats, usually 30-40 minutes.

### PRECAUTIONARY STATEMENTS:

#### KEEP OUT OF REACH OF CHILDREN

For institutional or commercial use.

**CAUTION: Eye irritant.** May cause skin irritation. May cause respiratory irritation. Wear safety glasses and rubber gloves when handling. Wear protective footwear and clothing when applying to floor.

### FIRSTAID:

If splashed on skin or in eyes, flush with large quantities of water. If swallowed, drink two glasses of water. Call a physician. If inhaled, remove to fresh air. If not breathing, call 911 or ambulance, then administer artificial respiration, preferably mouth-to-mouth.

### DynaSol, Inc.

330 Pine Street  
Canton, Ma. 02021  
1-781-821-8888  
Chemical Emergency Response Number  
INFOTRAC 800-535-5053



This product meets the Green Seal™ environmental standard for industrial and institutional floor-care products based on its reduced human and aquatic toxicity and reduced smog production potential.