

ENVIRO-STRIP LO-PH

Technical Data Sheet

ENVIRONMENTALLY FRIENDLY LO-PH FLOOR STRIPPER

DESCRIPTION:

ENVIRO-STRIP is a non-ammoniated, butyl free, extra heavy duty floor stripper that will remove all metal cross linked finishes. ENVIRO-STRIP will also strip urethane assisted floor finishes. ENVIRO-STRIP is part of the SAFE WORLD™ line of ecologically safe products that are designed to protect the environment.

USES:

Stripping of resilient tile, marble and terrazzo. Not recommended for rubber, wood, cork or asphalt.

DILUTIONS:

For heavy buildup Dilute 1 gallon of ENVIRO-STRIP with 1 gallon of water

For normal stripping Dilute 1 gallon of ENVIRO-STRIP with 4 gallons of water

For light stripping Dilute 1 gallon of ENVIRO-STRIP With 10 gallons of water

Diluting with hot water will increase activity

LIQUID PROPERTIES:

DIRECTIONS:

1 Apply diluted solution liberally to floor surface.

CONCENTRATE pH....	9.0-10.0
COLOR.....	Pale green
DENSITY.....	8.4 #/GAL
FLAMMABILITY.....	Non-Flammable
SHELF LIFE.....	1 Year 22°C 30 Days 50°C
STABILITY.....	Freeze-Thaw Stable
ODOR.....	Mild Characteristic Odor

- DO NOT treat more than 250 sq ft at one time
- Allow solution to remain on floor for 2-5 minutes before scrubbing
- Scrub thoroughly using either black, brown or high productivity pads.
- Remove solution with wet vacuum or auto scrubber.
- RINSE FLOOR THOROUGHLY WITH COLD WATER.

CAUTIONS:

Contains Monoethanolamine (CAS#141-43-5)

Wear rubber gloves and eye protection when using this product.

Not recommended for use on rubber, asphalt or hardwood floors.

KEEP OUT OF THE REACH OF
CHILDREN

EMERGENCY ACTIONS:

If ingested, do not induce vomiting. Drink water or milk and seek medical attention at once! If eye is contacted, flush with water and seek medical help. For external skin contact, remove contaminated clothing and wash thoroughly with water.



DYNASOL
330 PINE STREET
CANTON, MA 02021
(781-821-8888)